


All Pages Of This Edition Approved

Signature:



Date:

REV.	DESCRIPTION	REVISER	DATE
A0	First	luojinwei	2018-01-08



Specifications:

1. Display : OLED(WHITE).
2. Dot Matrix: 128*64
3. Dot Size: 0.154*0.154mm
4. Dot Pitch: 0.17*0.17mm
5. Aperture Rate: 78%
6. Active Area : 21.744*10.864mm
7. Drive IC: SSD1306
8. FPC P/N: FPC-HP12864-21-A0



PIN	SYMBOL
1	NC(GND)
2	C2P
3	C2N
4	C1P
5	C1N
6	VBAT
7	NC
8	VSS
9	VDD
10	BS0
11	BS1
12	BS2
13	CS#
14	RES#
15	D/C#
16	R/W#
17	E#
18	D0
19	D1
20	D2
21	D3
22	D4
23	D5
24	D6
25	D7
26	IREF
27	VCOMH
28	VCC
29	VLSS
30	NC(GND)

Shenzhen Osprey Optoelectronics Technology Co., Ltd.

Unspecified Tolerance:	±0.20	UNITS: mm	DATE:	MODEL NUMBER :		SHEET:	1 OF 1
DESIGN BY:	luojinwei	2018-01-08		OED096-12864W102-C30		SCALE:	1 : 1
CHECKED BY:				DO NOT SCALE THIS DRAWING.			
APPROVED BY:					PROJECTION		